





RAL 7040 - Window grey

Available in a wide range of RAL colours

RAL 7039 – Quartz grey

RAL 7016 – Anthracite grey

Aluminium Decking

In line with BS 8579:2020 guidance, Balco provide a well-engineered and non-combustible aluminium deck system, whilst also providing the end-user with a durable, long-lasting and low maintenance product. The decking boards are specially developed to withstand all weathering conditions, with a hard-wearing and anti-slip surface.

- Coarser particle texture for improved slip resistance in dry and wet conditions
- ≥60 PTV (dry) and ≥50 PTV (wet) in accordance with BS7976-2 +A1 2013 (solid colors)
- A2fl or A2,s1-d0 classified
- Qualicoat Class 1 & 2 compliant
- Minimum order quantity of 50kgs for solid shades
- Complies with Part B UK building regulations
- No warping or rotting issues associated with traditional timber decking


Easily assembled, Balco's decking has been designed for every application, and works seamlessly with Balco's Levitate[®] balcony drainage system, ensuring compliance with recognised Guarantee Providers.

Balco's decking is available in three Classic RAL colours as standard, although other colours can be considered


- Sustainable & recyclable material
- Reduced maintenance
- Qualicoat coating material compliant with EN 12206
- Improved aesthetics

Independant tests also meet or exceed:


- ISO 1519 (cylindrical Mandrel)
- ISO 2409 (2mm crosshatch)
- ISO 1520
- ISO 6272:1993
- ISO 2815



After the main profile is fastened, the open section is covered by clicking the secondary profile into place.



Free span width for the aludecking profiles is 800mm, which fulfills the load resistance and deflection requirements found in BS8579:2020



Europe's leading provider of end-to-end balcony solutions. Balconies for greater living.

www.balcouk.com











Balco Balcony Systems Ltd The Wagon House, Prockters Farm West Monkton, Taunton TA2 80N United Kingdom BALCONIES FOR GREATER LIVING

Phone +44 (0)2036 871020